Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Sales No. : 30261985

HINOKI WOOD MOD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Intended Use Fragrances : Perfume compound

1.3 Details of the supplier of the safety data sheet

Company

Givaudan Suisse SA Chemin de la Parfumerie 5 CH-1214 VERNIER

Telephone : +41227809111 Telefax : +41227809150

E-mail address : global.sds_info@givaudan.com

Responsible/issuing person

1.4 Emergency Call

Givaudan 24/7 call : +33172110003

Please refer to section 16 for a full list of emergency phone numbers, from Givaudan's 24/7 provider.

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION about classification, labeling and packaging of substances and mixtures No 28848)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, H411: Toxic to aquatic life with long lasting effects.

Category 2

2.2 Label elements

Labelling (REGULATION about classification, labeling and packaging of substances and mixtures No 28848)

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024

Print Date 07 MAY 2024

Hazard pictograms





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P391 Collect spillage.

Hazardous components which must be listed on the label:

 2-acetyl-1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetra-methylnaphtalene

(main isomer)

linalool 78-70-62,6,6,8-Tetramethyl 77-54-3

tricyclo(5.3.1.0(1.5))undecan-8-yl acetate

(R)-p-mentha-1,8-diene 5989-27-5
• Eucalyptus oil 8000-48-4
• Cedryl methyl ether 19870-74-7

Oils, Lemon 8008-56-86,7-Dihydro-1,1,2,3,3-pentamethyl- 33704-61-9

4(5H)-indanone

• 2,4-dimethylcyclohex-3-ene-1- 68039-49-6

carbaldehyde

2.3 Other hazards

Hazards not Otherwise : May cause phototoxicity.

Classified.

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3. Composition/information on ingredients

3.2 Mixtures

Hazardous components

| Chemical name | CAS-No. EC-No. Registration number | Classification (Regulation TR 28848) | Concentration [%] |
|---|---|---|-------------------|
| 2-acetyl-1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetra-methylnaphtalene (main isomer) | 54464-57-2 915-730-3 | Skin Irrit. 2; H315 Skin Sens. 1B; H317 Aquatic Chronic 2; H411 —————————————————————————————————— | >= 10 - < 20 |
| linalool | 78-70-6 201-134-4 | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity estimate Acute oral toxicity: 2 790,00 mg/kg | >= 5 - < 10 |
| 2,6-dimethyl-7-octen-2-ol | 18479-58-8 242-362-4 | Skin Irrit. 2; H315 Eye Irrit. 2; H319 | >= 1 - < 5 |

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Givaudan

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

| | | Acute toxicity estimate | |
|--|---------------------------------------|--|--------------|
| | | Acute oral toxicity: 3 600,00 mg/kg | |
| 2,6,6,8-Tetramethyl tricyclo(5.3.1.0(1.5))undecan-8-yl acetate | 77-54-3 201-036-1 | Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 | >= 2,5 - < 5 |
| | | Acute toxicity estimate Acute oral toxicity: > 5 000,00 mg/kg Acute dermal toxicity: > 5 000,00 mg/kg | |
| (R)-p-mentha-1,8-diene | 5989-27-5 227-813-5 | Flam. Liq. 3; H226 Skin Irrit. 2; H315 Skin Sens. 1B; H317 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 3; H412 | >= 2,5 - < 5 |
| | | Acute toxicity estimate Acute oral toxicity: 5 600,00 mg/kg Acute dermal toxicity: > 5 000,00 mg/kg | |
| Cedryl methyl ether | 19870-74-7 67874-81-1 243-384-7 | Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; | >= 1 - < 2,5 |

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Givaudan

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

| | | H410 | |
|--|--|--|--------------|
| | | M-Factor (Acute aquatic toxicity): 1 | |
| | | Acute toxicity estimate | |
| | | Acute oral toxicity: > 5 000,00 mg/kg Acute dermal toxicity: > 5 000,00 mg/kg | |
| Eucalyptus oil | 8000-48-4 84625-32-1 283-406-2 | Flam. Liq. 3; H226 Skin Irrit. 2; H315 Skin Sens. 1; H317 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 | >= 1 - < 2,5 |
| | | Acute toxicity estimate | |
| | | Acute oral toxicity: 4 440 mg/kg | |
| [3R-(3a,3aß,6a,7ß,8aa)]-octahydro- 3,6,8,8-tetramethyl-1H-3a,7- methanoazulen-6-ol | 77-53-2 201-035-6 | Aquatic Chronic 2; H411 | >= 1 - < 2,5 |
| | | Acute toxicity estimate | |
| | | Acute oral toxicity: > 5 000,00 mg/kg Acute dermal toxicity: > 5 000,00 mg/kg | |
| 0.11 | 2000 50 0 | > 5 000,00 mg/kg | 4 0.5 |
| Oils, Lemon | 8008-56-8 84929-31-7 284-515-8 01-0000490212-27 | Flam. Liq. 3; H226 Skin Irrit. 2; H315 Skin Sens. 1; H317 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 | >= 1 - < 2,5 |
| | | Acute toxicity estimate | |
| | | Acute dermal toxicity: > 5 000,00 mg/kg | |

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Givaudan

HINOKI WOOD MOD

THINOIN WOOD MOD

Version 2.0 Revision Date 07 MAY 2024

Print Date 07 MAY 2024

| 6,7-Dihydro-1,1,2,3,3-pentamethyl-4(5H)-indanone | 33704-61-9 251-649-3 | Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Aquatic Chronic 2; H411 Acute toxicity estimate Acute oral toxicity: 2 900,00 mg/kg | >= 0,25 - < 1 |
|--|-------------------------|--|--------------------|
| alpha cedrene | 469-61-4 207-418-4 | Skin Irrit. 2; H315 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10 Acute toxicity estimate Acute oral toxicity: > 5 000,00 mg/kg Acute dermal toxicity: > 5 000,00 | >= 0,25 - < 1 |
| 2,4-dimethylcyclohex-3-ene-1-carbaldehyde | 68039-49-6 943-728-2 | mg/kg Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411 Acute toxicity estimate Acute oral toxicity: > 3 100,00 mg/kg Acute dermal toxicity: 5 000,00 mg/kg | >= 0,1 - < 0,25 |

For the full text of the H-Statements mentioned in this Section, see Section 16.

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

SECTION 4. First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Immediately flush eyes for at least 15 minutes. Get medical

attention.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : no data available

Risks : Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : no data available

SECTION 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry chemical

Alcohol-resistant foam Carbon dioxide (CO2)

Water spray

Unsuitable extinguishing

media

: no data available

5.2 Special hazards arising from the substance or mixture

Specific hazards during : Do not allow run-off from fire fighting to enter drains or water

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

firefighting courses.

5.3 Advice for firefighters

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

: no data available

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

Not applicable

SECTION 7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Temperature class Fire-fighting class

: no data available : no data available

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

Dust explosion class : no data available

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on

: Ambient / 10-30℃ (50-85℃)

storage conditions

Dry, well ventilated, preferably full, hermetically sealed

Advice on common storage Storage class (TRGS 510) : Protect against light.: 10 Combustible liquids

Other data

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : no data available

SECTION 8. Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Exposure assessment: Exposures are dependent on the product being handled, the potential for chemical release, and any resulting airborne concentrations or dermal contact. Since product handling and release scenarios vary, and no two workplaces are exactly alike, it is recommended that the potential for exposure be assessed prior to the prod-uct's use or introduction. Exposure assessments should be performed by an occupational hygienist, industrial hygienist, or other qualified occupational or environmental health professional. An exposure assessment should be conducted to determine the efficacy of any ventilation and the need for additional PPE. The PPE indicated below are recommendations for worst-case scenario exposures. An exposure assessment will identify more applicable measures to be implemented. EN and ANSI standards are mentioned in the following recommendations, consult equivalent local standards when required.

PPE is always the last resort to avoid exposure. In any case technical and organisational measures have to be explored and used prior to the selection of PPE. The PPE selection is for operators trained to work with chemicals according to good industrial hygiene and safety practice. Operators have to be trained on the use of PPE.

8.2.1 Engineering measures

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024

Print Date 07 MAY 2024

Use engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use the product only with adequate ventilation.

8.2.2 Personal protective equipment

Eye/face protection : Use safety goggles and faceshield tested according to EN

166/ ANSI Z87.1 or equivalent local standard.

Hand protection : Use gloves when handling substance in open systems.

Inspect gloves prior to use. Train operators for proper use. If only incidental exposure is expected: (work without direct contact to substance) use gloves tested according EN 16523-1/ASTM F739 or equivalent local standard breakthrough times at least 10 minutes, tested for chemicals indicated in chapter 3

of this SDS. Change gloves frequently.

If direct skin contact is expected: use gloves tested according to EN 16523-1/ASTM F739 or equivalent local standard, tested for chemicals indicated in chapter 3 of this SDS.

Permeation time must exceed contact time.

Other skin protection : Wear working clothes covering arms and legs.

The type of protective equipment must be selected according to the concentration and amount of the hazardous substance at the specific workplace. Use apron and sleeve covers or

complete chemical suit if exposure is expected.

Respiratory protection : Respiratory protection should be worn when workplace

exposures exceed exposure limit requirements or guidelines. If there are no applicable exposure limits or guidelines, use an approved respirator where there is a potential for adverse effects, including but not limited to respiratory irritation or odor, or where indicated by the exposure assessment. Selection of air-purifying or positive-pressure supplied-air will depend on the results of the exposure assessment which includes an evaluation of the specific operations and the potential airborne concentrations. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

In case a risk analysis proved the cartridge respirator as

acceptable, use type:

ABEK-P3 (EN 14387) OR Combination Multi-gas/P100 (42CFR84.193; ANSI Z88.7 or equivalent local standard) as a

backup to engineering controls.

In absence of engineering controls, use self-contained breathing apparatus or full face supplied air respirators. Use respirators and components tested and approved under appropriate government standards such as CEN (EU) or

NIOSH 42 CFR 84(US).

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2



Regulation, 23.06.2017, No: 30105

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

Thermal hazards : Wear appropriate thermal protective clothing, when

necessary.

Hygiene measures : Remove contaminated clothing and protective equipment

before entering eating areas.

Do not eat, drink or smoke during work.

Wash hands any time after handling the product.

8.2.3 Environmental exposure controls

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid : Clear liquid Form

: Pale vellow to vellow Colour Taste : not determined Odour : woody, Citrus-like Odour Threshold : Not applicable

Flash point : 81 °C Method: Grabner miniflash closed cup

Lower explosion limit : not determined Upper explosion limit : not determined Flammability Flammability : Not applicable
Particle size : no data available
Oxidizing properties : not determined
Auto-ignition temperature : not determined
Decomposition temperature : no data available : not determined

: not determined

Boiling point : not determined

Vapour pressure : 0,151 hPa at 20 °C Calculated (99,9 %)

Density : 968,25 kg/m3 at 20 °C

Bulk density : Not applicable

Water solubility : not determined

Solubility/qualitative : not determined

Partition coefficient: n- : Not applicable

octanol/water

Boiling point

Viscosity, kinematic Relative vapour density : no data available : no data available Evaporation rate : no data available Explosive properties : no data available

9.2 Other information

Not applicable

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

SECTION 10. Stability and reactivity

10.1 Reactivity

none

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : no data available

10.5 Incompatible materials

Materials to avoid : no data available

10.6 Hazardous decomposition products

Hazardous decomposition

: no data available

products

Thermal decomposition : no data available

SECTION 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity : No data is available on the product itself.

Acute oral toxicity

2-acetyl-1,2,3,4,5,6,7,8octahydro-2,3,8,8-tetra: LD50: > 5 000 mg/kg

Species: Rat

methylnaphtalene (main

isomer)

linalool : LD50: 2 790 mg/kg Species: Rat

2,6-dimethyl-7-octen-2-ol

: LD50: 3 600 mg/kg

Species: Rat

2,6,6,8-Tetramethyl

: LD50: > 5 000 mg/kg

Species: Rat

tricyclo(5.3.1.0(1.5))undecan-

8-yl acetate

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Givaudan

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

(R)-p-mentha-1,8-diene : LD50: 5 600 mg/kg Species: Mouse

Cedryl methyl ether : LD50: > 5 000 mg/kg Species: Rat

Eucalyptus oil : LD50: 4 440 mg/kg Species: Rat

octahydro-3,6,8,8tetramethyl-1H-3a,7methanoazulen-6-ol

pentamethyl-4(5H)-indanone

alpha cedrene : LD50: > 5 000 mg/kg Species: Rat

1-carbaldehyde

Acute inhalation toxicity : No data is available on the product itself.

Acute dermal toxicity : No data is available on the product itself.

Acute dermal toxicity

octahydro-2,3,8,8-tetramethylnaphtalene (main

isomer)

2,6,6,8-Tetramethyl : LD50: > 5 000 mg/kg Species: Rabbit

tricyclo(5.3.1.0(1.5))undecan-

8-yl acetate

(R)-p-mentha-1,8-diene : LD50: > 5 000 mg/kg Species: Rabbit

Cedryl methyl ether : LD50: > 5 000 mg/kg Species: Rabbit

octahydro-3,6,8,8tetramethyl-1H-3a,7methanoazulen-6-ol

ernanoazuren-o-or

LD50: > 5 000 mg/kg Species: Rat

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2



Regulation, 23.06.2017, No: 30105 HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

Oils, Lemon : LD50: $> 5\,000\,\text{mg/kg}$ Species: Rabbit

alpha cedrene : LD50: > 5000 mg/kgSpecies: Rabbit

2,4-dimethylcyclohex-3-ene-

1-carbaldehyde

: LD50: 5 000 mg/kg Species: Rabbit

of administration)

Acute toxicity (other routes : No data is available on the product itself.

Skin corrosion/irritation

Skin irritation : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Eye irritation : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Respiratory or skin sensitisation

Sensitisation : No data is available on the product itself.

Germ cell mutagenicity

Germ cell mutagenicity : No data is available on the product itself.

Carcinogenicity

Carcinogenicity : No data is available on the product itself.

Reproductive toxicity

Not classified based on available information.

Target Organ Systemic Toxicant - Single exposure

Target Organ Systemic : No data is available on the product itself.

Toxicant - Single exposure

Target Organ Systemic Toxicant - Repeated exposure

Target Organ Systemic

Toxicant - Repeated

exposure

: No data is available on the product itself.

Target Organ Systemic Toxicant - Repeated exposure

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

Aspiration hazard

Aspiration toxicity : No data is available on the product itself.

Phototoxicity

Phototoxicity : No data is available on the product itself.

Further information : no data available

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks : no data available

SECTION 12. Ecological information

12.1 Toxicity

Components:

[3R-(3alpha,3abeta,6alpha,7beta,8aalpha)]-octahydro-3,6,8,8-tetramethyl-1H-3a,7-methanoazulen-5-yl acetate:

M-Factor (Acute aquatic

toxicity)

: 1

M-Factor (Chronic aquatic

: 1

toxicity)

[3R-(3alpha,3abeta,6beta,7beta,8aalpha)]-octahydro-6-methoxy-3,6,8,8-tetramethyl-1H-3a,7-

methanoazulene:

M-Factor (Acute aquatic

: 1

toxicity)

[3R-(3alpha,3abeta,7beta,8aalpha)]-2,3,4,7,8,8a-hexahydro-3,6,8,8-tetramethyl-1H-3a,7-methanoazulene:

M-Factor (Acute aquatic : 10

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

toxicity)

M-Factor (Chronic aquatic : 10

toxicity)

12.2 Persistence and degradability

no data available

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological

information

: Toxic to aquatic life with long lasting effects.

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

SECTION 13. Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

Do not re-use empty containers.

Dispose of in accordance with local regulations.

SECTION 14. Transport information

14.1 UN number

ADR : UN 3082 **IMDG** : UN 3082 **IATA** : UN 3082

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(alpha-Cedrene, Cedryl acetate)

: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, **IMDG**

N.O.S.

(alpha-Cedrene, Cedryl acetate)

IATA : Environmentally hazardous substance, liquid, n.o.s.

(alpha-Cedrene, Cedryl acetate)

14.3 Transport hazard class(es)

ADR 9 **IMDG** 9 **IATA** 9

14.4 Packing group

ADR Ш **IMDG** Ш **IATA** Ш

14.5 Environmental hazards

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

14.6 Special precautions for user

ADR

Tunnel restriction code : (-)

IMDG

IMDG Code Segregation : None

Group

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Major Accident Hazard : ENVIRONMENTAL HAZARDS

Legislation E

Quantity 1: 200 t Quantity 2: 500 t

Water hazard class : WGK 3 highly hazardous to water

(Germany) Classification according to AwSV, Annex 1 (5.2)

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16. Other information

Full text of H-Statements

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
 H411 : Toxic to aquatic life with long lasting effects.
 H412 : Harmful to aquatic life with long lasting effects.

Full list of Emergency response numbers worldwide.

| | Country | Phone nr | | Country | Phone nr |
|--------|------------|-----------------|------|-----------------------------|---------------|
| Europe | All Europe | +44 1235 239670 | APAC | All East/South East Asia | +65 3158 1074 |

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024 Print Date 07 MAY 2024

| | I | 1 | İ | I | ı |
|-----------------------|----------------------------|----------------------------------|-------|-------------|-----------------------------------|
| | France | +33 1 72 11 00 03 | | Sri Lanka | +65 3158 1195 |
| | Germany | +49 89 220 61012 | | Taiwan | +886 2 8793 3212 |
| | Spain | +34 91 114 2520 | | Japan | 0120 015 230 |
| | Italy | 800 699 792 | | Indonesia | 007 803 011 0293 |
| | Netherlands | +31 10 713 8195 | | Malaysia | +60 3 6207 4347 |
| | Turkey | 0800 621 2139 +44 1235 239670 | | Thailand | 001 800 120 666 751 |
| | Norway | +47 2103 4452 | | India | +65 3158 1198 000 800 100 7479 |
| | Greece | +30 21 1198 3182 | | Pakistan | +65 3158 1329 |
| | Portugal | +351 30880 4750 | | Bangladesh | +65 3158 1200 |
| | Denmark | +45 8988 2286 | | Philippines | +63 2 8231 2149 |
| | Sweden | +46 8 566 42573 | | Vietnam | +84 28 4458 2388 |
| | Poland | +48 22 307 3690 | | Korea | +65 3158 1285 |
| | Czech replublic | +420 228 882 830 | | South Korea | +82 2 3479 8401 |
| | Finland | +358 9 7479 0199 | | Australia | +61 2 8014 4558 |
| | All Middle East/Africa | +44 1235 239671 | | New Zealand | +64 9 929 1483 |
| Middle East/Africa | Bahrain and Middle East | +44 1235 239671 | | China | +86 532 8388 9090 |
| | Africa/South Africa | +27 21 300 2732 | | Mexico | +52 55 5004 8763 |
| NOAM | USA and Canada | +1 866 928 0789 | | Brazil | +55 11 3197 5891 |
| | USA and Canada | +1 215 207 0061 | LATAM | Chile | +56 2 2582 9336 |
| | USA and Canada | +1 202 464 2554 | | Colombia | +57 1 508 7337 |
| Global | Global | +44 1865 407333 | | Argentina | +54 11 5984 3690 |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Information displayed in section 3 (Composition/information on ingredients) is additional information to understand the hazards of the product and ensure safe handling, storage and transportation. This information, including CAS numbers, is not meant to be used for registration, notification or any other purposes. Any additional information and documentation needed may be provided by Givaudan.

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Givaudan

HINOKI WOOD MOD

Version 2.0 Revision Date 07 MAY 2024

Print Date 07 MAY 2024

| Prepared b | Ì۱ | 1 |
|------------|----|---|
|------------|----|---|

Name Surname: Esra Kurtoğlu

Contact Information: esra.purcek@givaudan.com

Certification Number: KDU-A-0-0250

Administrative information: