Prepared in accordance with the provisions of KKDIK Annex-2



Regulation, 23.06.2017, No: 30105

# **SEA STONE MOD**

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Sales No. : EAK46659/00

SEA STONE MOD

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Intended Use Fragrances : Perfume compound

### 1.3 Details of the supplier of the safety data sheet

Company

Givaudan Suisse SA Chemin de la Parfumerie 5 CH-1214 VERNIER

Telephone : +41227809111 Telefax : +41227809150

E-mail address : global.sds\_info@givaudan.com

Responsible/issuing person

# 1.4 Emergency Call

Givaudan 24/7 call : +33172110003

Please refer to section 16 for a full list of emergency phone numbers, from Givaudan's 24/7 provider.

# SECTION 2. Hazards identification

#### 2.1 Classification of the substance or mixture

Classification (REGULATION about classification, labeling and packaging of substances and mixtures No 28848)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, H411: Toxic to aquatic life with long lasting effects.

Category 2

#### 2.2 Label elements

Labelling (REGULATION about classification, labeling and packaging of substances and mixtures No 28848)

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

# Regulation, 23.06.2017, No: 30105 SEA STONE MOD

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

Hazard pictograms





Signal word Warning

Hazard statements H315 Causes skin irritation.

> H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Toxic to aquatic life with long lasting effects. H411

Precautionary statements **Prevention:** 

P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face

protection.

Response:

If skin irritation or rash occurs: Get medical P333 + P313

advice/ attention.

P391 Collect spillage.

Hazardous components which must be listed on the label:

2-acetyl-1,2,3,4,5,6,7,8-octahydro-54464-57-2 2,3,8,8-tetra-methylnaphtalene

(main isomer)

benzyl salicylate 118-58-1 linalool 78-70-6 3.7-dimethyl-1.6-octadien-3-vl 115-95-7

acetate (= linalyl acetate)

2,6,6,8-tetramethyl-9-acetyl-32388-55-9

tricyclo{5.3.1.0(1,5)}undec-8-ene

(R)-p-mentha-1,8-diene 5989-27-5 Cedryl methyl ether 19870-74-7 Cyclopentadecanolide 106-02-5 4-tert-butylcyclohexyl acetate 32210-23-4 2-hexyl-3-phenyl-2-propenal (trans & 101-86-0

Mandarin orange, extract 8008-31-9 rosemary oil 8000-25-7 3-(3,4-Methylene dioxyphenyl)-2-1205-17-0

methylpropanal

cis-4-13828-37-0

(isopropyl)cyclohexanemethanol

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2



Regulation, 23.06.2017, No: 30105 SEA STONE MOD

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

#### 2.3 Other hazards

Hazards not Otherwise : None

Classified.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SECTION 3. Composition/information on ingredients

#### 3.2 Mixtures

### **Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification (Regulation TR 28848)	Concentration [%]
2-acetyl-1,2,3,4,5,6,7,8-octahydro-2,3,8,8-tetra-methylnaphtalene (main isomer)	54464-57-2 915-730-3	Skin Irrit. 2; H315 Skin Sens. 1B; H317 Aquatic Chronic 2; H411 ——————————————————————————————————	>= 10 - < 20
benzyl salicylate	118-58-1 204-262-9 01-0000468590-37	Eye Irrit. 2; H319 Skin Sens. 1B; H317 Aquatic Chronic 3; H412 Acute toxicity	>= 5 - < 10

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Givaudan

**SEA STONE MOD** 

Version 3.0 Revision Date 23 FEB 2024

Print Date 07 MAY 2024

		estimate	
		Acute oral toxicity: 2 227,00 mg/kg Acute dermal toxicity: 14 150,00 mg/kg	
linalool	78-70-6 201-134-4	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Acute toxicity estimate  Acute oral toxicity: 2 790,00 mg/kg	>=1-<5
3,7-dimethyl-1,6-octadien-3-yl acetate (= linalyl acetate)	115-95-7 204-116-4	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1B; H317 ————————————————————————————————————	>= 1 - < 5
2,6,6,8-tetramethyl-9-acetyl- tricyclo{5.3.1.0(1,5)}undec-8-ene	32388-55-9 251-020-3 01-0000479672-25	Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 ——— M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 ———— Acute toxicity	>= 2,5 - < 5
		Acute oral toxicity: > 5 000,00 mg/kg	

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Givaudan

**SEA STONE MOD** 

Version 3.0 Revision Date 23 FEB 2024

Print Date 07 MAY 2024

oxacyclohexadec-13-en-2-one; a) (Z)-oxacyclohexadec-(12)-en-2-one and b) (Z)-oxacyclohexadec-(13)-en-	422-320-3	Aquatic Chronic 1; H410	
2-one		M-Factor (Acute aquatic toxicity): 1	
4-(1-Ethoxyvinyl)-3,3,5,5- tetramethyl-cyclohexan-1-one (main component)	36306-87-3 252-961-2 01-0000457151-73	Skin Irrit. 2; H315 Aquatic Chronic 2; H411	>= 1 - < 2,5
		Acute toxicity estimate	
		Acute dermal toxicity: > 5 000,00 mg/kg	
(R)-p-mentha-1,8-diene	5989-27-5 227-813-5	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Skin Sens. 1B; H317 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 3; H412	>= 1 - < 2,5
		Acute toxicity estimate  Acute oral toxicity:	
		5 600,00 mg/kg Acute dermal toxicity: > 5 000,00 mg/kg	
Cedryl methyl ether	19870-74-7 67874-81-1 243-384-7	Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2,5
		M-Factor (Acute aquatic toxicity): 1	
		Acute toxicity estimate	
		Acute oral toxicity: > 5 000,00 mg/kg Acute dermal toxicity: > 5 000,00	

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Givaudan

**SEA STONE MOD** 

Version 3.0 Revision Date 23 FEB 2024

Print Date 07 MAY 2024

		mg/kg	
Cyclopentadecanolide	106-02-5 203-354-6	Skin Sens. 1B; H317 Aquatic Chronic 2; H411	>= 1 - < 2,5
		Acute toxicity estimate	
		Acute oral toxicity: > 5 000,00 mg/kg Acute dermal toxicity: > 5 000,00 mg/kg	
4-tert-butylcyclohexyl acetate	32210-23-4 250-954-9	Skin Sens. 1B; H317	>= 1 - < 5
		Acute toxicity estimate	
		Acute oral toxicity: 3 370 mg/kg Acute dermal toxicity: > 5 000,00 mg/kg	
2-hexyl-3-phenyl-2-propenal (trans & cis)	101-86-0 165184-98-5 639-566-4 01-0000466934-37	Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0,25 - < 1
		M-Factor (Acute aquatic toxicity): 1	
		Acute toxicity estimate	
		Acute oral toxicity: 3 100,00 mg/kg	
cis-3-hexenyl 2-hydroxybenzoate	65405-77-8 265-745-8	Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0,25 - < 1
		M-Factor (Acute aquatic toxicity): 1	
		Acute toxicity estimate	

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Givaudan

**SEA STONE MOD** 

Version 3.0 Revision Date 23 FEB 2024

Print Date 07 MAY 2024

		Acute oral toxicity: > 5 000,00 mg/kg Acute dermal toxicity: > 5 000,00 mg/kg	
Mandarin orange, extract	8008-31-9 84929-38-4 284-521-0	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Skin Sens. 1; H317 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 ——————————————————————————————————	>= 0,25 - < 1
		Acute oral toxicity: > 5 000,00 mg/kg Acute dermal toxicity: > 5 000,00 mg/kg	
rosemary oil	8000-25-7 84604-14-8 283-291-9	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1B; H317 STOT SE 2; H371 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 0,25 - < 1
		Acute toxicity estimate  Acute dermal	
		toxicity: > 9 000,00 mg/kg	
3-(3,4-Methylene dioxyphenyl)-2- methylpropanal	1205-17-0 214-881-6	Skin Sens. 1B; H317 Repr. 2; H361 Aquatic Chronic 2; H411	>= 0,1 - < 0,25
		Acute toxicity estimate  Acute oral toxicity: 3 561,00 mg/kg	
1-methyl-4(3)-(4-methyl-3-pentenyl)- 3-cyclohexene-1-carbaldehyde	52475-86-2 52474-60-9	Aquatic Acute 1; H400	>= 0,1 - < 0,25

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Givaudan

**SEA STONE MOD** 

Version 3.0 Revision Date 23 FEB 2024

Print Date 07 MAY 2024

	915-712-5	Aquatic Chronic 1; H410	
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
2,6-bis(1,1-dimethylethyl)-4- methylphenol	128-37-0 204-881-4	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 ————————————————————————————————————	>= 0,1 - < 0,25
		aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
		Acute toxicity estimate	
		Acute dermal toxicity: > 5 000,00 mg/kg	
Pentyl 2-hydroxybenzoate	2050-08-0 218-080-2 01-0000468587-13	Acute Tox. 4; H302 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,1 - < 0,25
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
		Acute toxicity estimate	
		Acute oral toxicity: 2 000 mg/kg	
2-propenyl 2(3)-methylbutoxyacetate	67634-00-8 67634-01-9 916-328-0	Acute Tox. 4; H302 Acute Tox. 2; H330 Acute Tox. 4; H312 Aquatic Acute 1; H400	>= 0,1 - < 0,25
		M-Factor (Acute aquatic toxicity): 1	

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

# **SEA STONE MOD**

Version 3.0 Revision Date 23 FEB 2024

Print Date 07 MAY 2024

		Acute toxicity estimate  Acute oral toxicity:	
cis-4-	13828-37-0	730,00 mg/kg Skin Irrit. 2; H315	>= 0,1 - < 1
(isopropyl)cyclohexanemethanol	5502-75-0 939-719-8	Skin Sens. 1B; H317	>= 0,1 - < 1
		Acute toxicity estimate	
		Acute oral toxicity: > 10 000,00 mg/kg	

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### **SECTION 4. First aid measures**

# 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Remove contact lenses.

Immediately flush eyes for at least 15 minutes. Get medical

attention.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : no data available

Risks : Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2



Regulation, 23.06.2017, No: 30105

# **SEA STONE MOD**

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : no data available

# SECTION 5. Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Dry chemical

Alcohol-resistant foam Carbon dioxide (CO2)

Water spray

Unsuitable extinguishing

media High volume water jet

# 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

#### 5.3 Advice for firefighters

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

### SECTION 6. Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : no data available

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

Not applicable

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2



Regulation, 23.06.2017, No: 30105

SEA STONE MOD

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

### SECTION 7. Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Dispose of rinse water in accordance with local and national

regulations.

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Temperature class : no data available Fire-fighting class : no data available Dust explosion class : no data available

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

: Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on

storage conditions

: Ambient / 10-30℃ (50-85年)
Dry, well ventilated, preferably full, hermetically sealed

Advice on common storage

: Protect against light.: 10 Combustible liquids

Storage class (TRGS 510) Other data

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : no data available

#### SECTION 8. Exposure controls/personal protection

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

Exposure assessment: Exposures are dependent on the product being handled, the

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2



Regulation, 23.06.2017, No: 30105

# **SEA STONE MOD**

Version 3.0 Revision Date 23 FEB 2024

Print Date 07 MAY 2024

potential for chemical release, and any resulting airborne concentrations or dermal contact. Since product handling and release scenarios vary, and no two workplaces are exactly alike, it is recommended that the potential for exposure be assessed prior to the prod-uct's use or introduction. Exposure assessments should be performed by an occupational hygienist, industrial hygienist, or other qualified occupational or environmental health professional. An exposure assessment should be conducted to determine the efficacy of any ventilation and the need for additional PPE. The PPE indicated below are recommendations for worst-case scenario exposures. An exposure assessment will identify more applicable measures to be implemented. EN and ANSI standards are mentioned in the following recommendations, consult equivalent local standards when required.

PPE is always the last resort to avoid exposure. In any case technical and organisational measures have to be explored and used prior to the selection of PPE. The PPE selection is for operators trained to work with chemicals according to good industrial hygiene and safety practice. Operators have to be trained on the use of PPE.

#### 8.2.1 Engineering measures

Use engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use the product only with adequate ventilation.

### 8.2.2 Personal protective equipment

Eye/face protection : Use safety goggles and faceshield tested according to EN

166/ ANSI Z87.1 or equivalent local standard.

Hand protection : Use gloves when handling substance in open systems.

Inspect gloves prior to use. Train operators for proper use. If only incidental exposure is expected: (work without direct contact to substance) use gloves tested according EN 16523-1/ASTM F739 or equivalent local standard breakthrough times at least 10 minutes, tested for chemicals indicated in chapter 3

of this SDS. Change gloves frequently.

If direct skin contact is expected: use gloves tested according to EN 16523-1/ASTM F739 or equivalent local standard, tested for chemicals indicated in chapter 3 of this SDS.

Permeation time must exceed contact time.

Other skin protection : Wear working clothes covering arms and legs.

The type of protective equipment must be selected according to the concentration and amount of the hazardous substance at the specific workplace. Use apron and sleeve covers or

complete chemical suit if exposure is expected.

Respiratory protection : Respiratory protection should be worn when workplace

exposures exceed exposure limit requirements or guidelines. If there are no applicable exposure limits or guidelines, use an approved respirator where there is a potential for adverse

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



**SEA STONE MOD** 

Version 3.0 Revision Date 23 FEB 2024

Print Date 07 MAY 2024

effects, including but not limited to respiratory irritation or odor, or where indicated by the exposure assessment. Selection of air-purifying or positive-pressure supplied-air will depend on the results of the exposure assessment which includes an evaluation of the specific operations and the potential airborne concentrations. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

In case a risk analysis proved the cartridge respirator as

acceptable, use type:

ABEK-P3 (EN 14387) OR Combination Multi-gas/P100 (42CFR84.193; ANSI Z88.7 or equivalent local standard) as a

backup to engineering controls.

In absence of engineering controls, use self-contained breathing apparatus or full face supplied air respirators. Use respirators and components tested and approved under appropriate government standards such as CEN (EU) or

NIOSH 42 CFR 84(US).

Thermal hazards : Wear appropriate thermal protective clothing, when

necessary.

Hygiene measures : Remove contaminated clothing and protective equipment

before entering eating areas.

Do not eat, drink or smoke during work.

Wash hands any time after handling the product.

#### 8.2.3 Environmental exposure controls

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

# SECTION 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid Form : liquid

Colour : Pale yellow to yellow Taste : not determined

Odour : Citrus-like, Marine, aromatic

Odour Threshold : Not applicable

Flash point : 94  $^{\circ}$  Method: Grabner miniflash closed cup

Lower explosion limit : not determined
Upper explosion limit : not determined
Flammability : Not applicable
Particle size : no data available
Oxidizing properties : no data available

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2



Regulation, 23.06.2017, No: 30105

# SEA STONE MOD

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

Auto-ignition temperature : not determined Decomposition temperature : no data available

: 0,0589 hPa at 20 ℃ Calculated (98,8 %)

pH : not data available

PH : not determined

PH :

octanol/water
Viscosity, kinematic
Relative vapour density : no data available : no data available Evaporation rate : no data available Explosive properties : no data available

#### 9.2 Other information

Not applicable

### SECTION 10. Stability and reactivity

### 10.1 Reactivity

none

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : no data available

10.5 Incompatible materials

Materials to avoid : no data available

#### 10.6 Hazardous decomposition products

Hazardous decomposition : no data available

products

Thermal decomposition : no data available

# SECTION 11. Toxicological information

#### 11.1 Information on toxicological effects

**Acute toxicity** 

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SEA STONE MOD

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

: LD50: > 5 000 mg/kg

**Acute oral toxicity** : No data is available on the product itself.

Acute oral toxicity

2-acetyl-1,2,3,4,5,6,7,8octahydro-2,3,8,8-tetramethylnaphtalene (main

isomer)

benzyl salicylate : LD50: 2 227 mg/kg Species: Rat

linalool : LD50: 2 790 mg/kg Species: Rat

3,7-dimethyl-1,6-octadien-3-

yl acetate (= linalyl acetate)

: LD50: > 5 000 mg/kg

: LD50: 13 934 mg/kg

Species: Rat

Species: Rat

Species: Rat

2,6,6,8-tetramethyl-9-acetyltricyclo{5.3.1.0(1,5)}undec-8-

ene

(R)-p-mentha-1,8-diene : LD50: 5 600 mg/kg Species: Mouse

Cedryl methyl ether : LD50: > 5000 mg/kg Species: Rat

Cyclopentadecanolide : LD50: > 5000 mg/kg Species: Rat

4-tert-butylcyclohexyl acetate : LD50: 3 370 mg/kg

Species: Rat

2-hexyl-3-phenyl-2-propenal

(trans & cis)

: LD50: 3 100 mg/kg

Species: Rat

cis-3-hexenyl 2-

hydroxybenzoate

: LD50: > 5 000 mg/kg

Species: Rat

Mandarin orange, extract : LD50: > 5 000 mg/kg Species: Rat

3-(3,4-Methylene dioxyphenyl)-2-

methylpropanal

: LD50: 3 561 mg/kg

Species: Rat

Species: Rat

Pentyl 2-hydroxybenzoate : LD50: 2 000 mg/kg

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105

Givaudan

SEA STONE MOD

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

2-propenyl 2(3)-: LD50: 730 mg/kg Species: Rat

methylbutoxyacetate

Species: Rat cis-4-: LD50: > 10 000 mg/kg

(isopropyl)cyclohexanemetha

Acute inhalation toxicity : Acute toxicity estimate Exposure time: 4 h

Dose: > 20,00 mg/l

: LD50: > 5 000 mg/kg

Method: Calculation method

**Acute dermal toxicity** : No data is available on the product itself.

**Acute dermal toxicity** 

2-acetyl-1,2,3,4,5,6,7,8octahydro-2,3,8,8-tetramethylnaphtalene (main

isomer)

benzyl salicylate : LD50: 14 150 mg/kg Species: Rabbit

3,7-dimethyl-1,6-octadien-3yl acetate (= linalyl acetate)

: LD50: > 5 000 mg/kg

Species: Rabbit

Species: Rabbit

4-(1-Ethoxyvinyl)-3,3,5,5tetramethyl-cyclohexan-1-

one (main component)

: LD50: > 5000 mg/kg

: LD50: > 5 000 mg/kg

Species: Rabbit

Species: Rabbit

(R)-p-mentha-1,8-diene Cedryl methyl ether

: LD50: > 5000 mg/kg

Species: Rabbit

Cyclopentadecanolide

: LD50: > 5000 mg/kg

Species: Rabbit

4-tert-butylcyclohexyl acetate

: LD50: > 5 000 mg/kg

Species: Rabbit

cis-3-hexenyl 2-

: LD50: > 5 000 mg/kg

Species: Rabbit

hydroxybenzoate

Mandarin orange, extract : LD50: > 5 000 mg/kg Species: Rabbit

rosemary oil : LD50: > 9000 mg/kg Species: Rabbit

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2



Regulation, 23.06.2017, No: 30105

# SEA STONE MOD

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

2,6-bis(1,1-dimethylethyl)-4-

methylphenol

: LD50: > 5000 mg/kg

Species: Rabbit

of administration)

**Acute toxicity (other routes**: No data is available on the product itself.

Skin corrosion/irritation

Skin irritation : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Eye irritation : Vapours may cause irritation to the eyes, respiratory system

and the skin.

Respiratory or skin sensitisation

Sensitisation : No data is available on the product itself.

Germ cell mutagenicity

Germ cell mutagenicity : No data is available on the product itself.

Carcinogenicity

Carcinogenicity : No data is available on the product itself.

Reproductive toxicity

Not classified based on available information.

Target Organ Systemic Toxicant - Single exposure

Target Organ Systemic

: No data is available on the product itself.

Toxicant - Single exposure

Target Organ Systemic Toxicant - Repeated exposure

Target Organ Systemic

Toxicant - Repeated

exposure

: No data is available on the product itself.

Target Organ Systemic Toxicant - Repeated exposure **Aspiration hazard** 

: No data is available on the product itself.

**Phototoxicity** 

Aspiration toxicity

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

# **SEA STONE MOD**

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

Phototoxicity : No data is available on the product itself.

Further information : no data available

#### 11.2 Information on other hazards

# **Endocrine disrupting properties**

**Product:** 

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

**Further information** 

Product:

Remarks : no data available

### SECTION 12. Ecological information

#### 12.1 Toxicity

### **Components:**

[3R-(3.alpha.,3a ,7 ,8a.alpha.)]-1-(2,3,4,7,8,8a-hexahydro-3,6,8,8-tetramethyl-1H-3a,7-methanoazulen-5-yl)ethan-1-one:

M-Factor (Acute aquatic :

toxicity)

M-Factor (Chronic aquatic :

toxicity)

**HABANOLIDE:** 

M-Factor (Acute aquatic : 1

toxicity)

[3R-(3alpha,3abeta,6beta,7beta,8aalpha)]-octahydro-6-methoxy-3,6,8,8-tetramethyl-1H-3a,7-methanoazulene:

M-Factor (Acute aquatic

toxicity)

: 1

alpha-hexylcinnamaldehyde:

M-Factor (Acute aquatic : 1

toxicity)

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2 Regulation, 23.06.2017, No: 30105



SEA STONE MOD

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

(Z)-3-hexenyl salicylate:

M-Factor (Acute aquatic

toxicity)

1-methyl-4-(4-methyl-3-pentenyl)cyclohex-3-ene-1-carbaldehyde: : 1

M-Factor (Acute aquatic

toxicity)

M-Factor (Chronic aquatic

toxicity)

2,6-di-tert-butyl-p-cresol:

M-Factor (Acute aquatic : 1

toxicity)

M-Factor (Chronic aquatic

toxicity)

pentyl salicylate:

M-Factor (Acute aquatic

toxicity)

M-Factor (Chronic aquatic

toxicity)

allyl (2-methylbutoxy)acetate:

M-Factor (Acute aquatic

toxicity)

12.2 Persistence and degradability

no data available

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product:

This substance/mixture contains no components considered Assessment

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

**Product:** 

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2



Regulation, 23.06.2017, No: 30105

# SEA STONE MOD

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

**Product:** 

Additional ecological

information

Toxic to aquatic life with long lasting effects.

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

### SECTION 13. Disposal considerations

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Dispose of in accordance with local regulations.

# SECTION 14. Transport information

# 14.1 UN number

ADR : UN 3082 IMDG : UN 3082 IATA : UN 3082

#### 14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

NOS

(Tetramethyl-acetyl-tricycloundecene, Cedryl methyl ether)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Tetramethyl-acetyl-tricycloundecene, Cedryl methyl ether)

IATA : Environmentally hazardous substance, liquid, n.o.s.

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2



Regulation, 23.06.2017, No: 30105

SEA STONE MOD

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

(Tetramethyl-acetyl-tricycloundecene, Cedryl methyl ether)

14.3 Transport hazard class(es)

 ADR
 : 9

 IMDG
 : 9

 IATA
 : 9

14.4 Packing group

14.5 Environmental hazards

**ADR** 

Environmentally hazardous : yes

MDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

**ADR** 

Tunnel restriction code : (-)

**IMDG** 

IMDG Code Segregation : None

Group

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

# SECTION 15. Regulatory information

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Major Accident Hazard : ENVIRONMENTAL HAZARDS

Legislation E2

Quantity 1: 200 t

Quantity 2: 500 t

Water hazard class : WGK 2 obviously hazardous to water

(Germany) Classification according to AwSV, Annex 1 (5.2)

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Regulation, 23.06.2017, No: 30105



Version 3.0 Revision Date 23 FEB 2024

Givaudan

Print Date 07 MAY 2024

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

#### **SECTION 16. Other information**

# **Full text of H-Statements**

H226 : Flammable liquid and vapour.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H319 : Causes serious eye irritation.

H330 : Fatal if inhaled.

H361 : Suspected of damaging fertility or the unborn child.

H371 : May cause damage to organs. H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

### Full list of Emergency response numbers worldwide.

	Country	Phone nr		Country	Phone nr
	All Europe	+44 1235 239670		All East/South East Asia	+65 3158 1074
	France	+33 1 72 11 00 03		Sri Lanka	+65 3158 1195
	Germany	+49 89 220 61012		Taiwan	+886 2 8793 3212
	Spain	+34 91 114 2520		Japan	0120 015 230
	Italy	800 699 792		Indonesia	007 803 011 0293
	Netherlands	+31 10 713 8195	APAC	Malaysia	+60 3 6207 4347
Europe	Turkey	0800 621 2139 +44 1235 239670		Thailand	001 800 120 666 751
	Norway	+47 2103 4452		India	+65 3158 1198 000 800 100 7479
	Greece	+30 21 1198 3182		Pakistan	+65 3158 1329
	Portugal	+351 30880 4750		Bangladesh	+65 3158 1200
	Denmark	+45 8988 2286		Philippines	+63 2 8231 2149
	Sweden	+46 8 566 42573		Vietnam	+84 28 4458 2388
	Poland	+48 22 307 3690		Korea	+65 3158 1285
	Czech replublic	+420 228 882 830		South Korea	+82 2 3479 8401

Administrative information:

Prepared in accordance with the provisions of KKDIK Annex-2

Givaudan

Regulation, 23.06.2017, No: 30105

# **SEA STONE MOD**

Version 3.0 Revision Date 23 FEB 2024 Print Date 07 MAY 2024

	Finland	+358 9 7479 0199		Australia	+61 2 8014 4558
Middle East/Africa	All Middle East/Africa	+44 1235 239671		New Zealand	+64 9 929 1483
	Bahrain and Middle East	+44 1235 239671		China	+86 532 8388 9090
	Africa/South Africa	+27 21 300 2732		Mexico	+52 55 5004 8763
	USA and Canada	+1 866 928 0789	LATAM	Brazil	+55 11 3197 5891
NOAM	USA and Canada	+1 215 207 0061		Chile	+56 2 2582 9336
	USA and Canada	+1 202 464 2554		Colombia	+57 1 508 7337
Global	Global	+44 1865 407333		Argentina	+54 11 5984 3690

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Information displayed in section 3 (Composition/information on ingredients) is additional information to understand the hazards of the product and ensure safe handling, storage and transportation. This information, including CAS numbers, is not meant to be used for registration, notification or any other purposes. Any additional information and documentation needed may be provided by Givaudan.

#### Prepared by

Name Surname: Esra Kurtoğlu

Contact Information: esra.purcek@givaudan.com

Certification Number: KDU-A-0-0250

Administrative information: